



MATERIAL SAFETY DATA SHEET

DIMETHYLAMINE (25-40% AQUEOUS SOLUTIONS)

SECTION 1- CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MSDS Name:
DIMETHYLAMINE (25-40% AQUEOUS SOLUTIONS)

Synonyms : methanamine, N-methyl
CAS No. : 124-40-3
Molecular Weight : 45.09
Chemical Formula : (CH₃)₂NH
Product Codes : Un Listed
J.T. Baker : J407
Mallinckrodt : 2393

Company Information:
LEONID CHEMICALS
62/A-2 1st Stage, Yeshwanthpur Industrial Suburb
Ashokpuram School Road
Bangalore-560 022, Karnataka, INDIA
Ph: +91-80-2337 8354, Fax: +91-80-2357 4827

SECTION 2- COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient : Dimethylamine
CAS No. : 124-40-3
% : 25 - 40 %
Hazardous : No

Ingredient : Water
CAS No. : 7732-18-5
% : 60 - 75%
Hazardous : No

SECTION 3- HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. CAUSES BURNS TO ANY AREA OF CONTACT.

Potential Health Effects

Inhalation:

Inhalation produces damaging effects on the mucous membranes and upper respiratory tract. Symptoms may include irritation of the nose and throat, and labored breathing. May cause lung edema, a medical emergency.

Ingestion:

Corrosive. Swallowing can cause severe burns of the mouth, throat, and stomach. Can

cause sore throat, vomiting, diarrhea.

Skin Contact:

Corrosive. Symptoms of redness, pain, and severe burn can occur. May be absorbed through the skin causing nausea, headache and general discomfort.

Eye Contact:

Vapors are highly irritating and can cause corneal damage. Contact with liquid can cause severe burns and blindness.

Chronic Exposure:

Chronic exposure may cause dermatitis, conjunctivitis, and lung problems.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders or eye problems or impaired respiratory function may be more susceptible to the effects of the substance.

SECTION 4- FIRST AID MEASURES

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician immediately.

Ingestion:

DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Call a physician immediately.

Skin Contact:

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician, immediately. Wash clothing before reuse.

Eye Contact:

Immediately flush eyes with gentle but large stream of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Call a physician immediately.

SECTION 5- FIRE FIGHTING MEASURES

Fire:

Flash point : -18C (0F)
Autoignition temperature : 430C (806F)
Flammable limits in air % by volume:
lcl: 2.8; ucl: 14.4
Extremely Flammable Liquid.

Explosion:

Above flash point, vapor-air mixtures are explosive within flammable limits noted above. Vapors can flow along surfaces to distant ignition source and flash back. Sensitive to static discharge.

Fire Extinguishing Media:

Stop flow before extinguishing fire. Dry chemical, alcohol foam or carbon dioxide. Water spray may be used to keep fire exposed containers cool.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

SECTION 6- ACCIDENTAL RELEASE MEASURES

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! Use water spray to reduce vapors and dilute spills to nonflammable mixtures.

SECTION 7 - HANDLING and STORAGE

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

Airborne Exposure Limits:

-OSHA Permissible Exposure Limit (PEL): 10 ppm (TWA)

-ACGIH Threshold Limit Value (TLV):

5 ppm (TWA), 15 ppm (STEL)

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a half-face respirator with an ammonia/methylamine cartridge may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece respirator with an ammonia/methylamine cartridge may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. The recommended cartridge is not specifically approved for this substance. Organic vapor cartridges have a service life of less than 30 minutes with this material.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

Other Control Measures:

There is insufficient data in the published literature to assign complete numerical SAF-T-DATA* ratings and laboratory protective equipment for this product. Special precautions must be used in storage, use and handling. Protective equipment for laboratory bench use should be chosen using professional judgment based on the size and type of reaction or test to be conducted and the available ventilation, with overriding consideration to minimize contact with the chemical.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Clear, colorless liquid.
Odor	:	Ammonia odor.
Solubility	:	Very soluble in water.
Specific Gravity	:	0.83 - 0.93
pH	:	Highly alkaline; (MASC.)
% Volatiles by volume @ 21C (70F)	:	100
Boiling Point	:	No information found.
Melting Point	:	No information found.
Vapor Density (Air=1)	:	No information found.
Vapor Pressure (mm Hg)	:	No information found.
Evaporation Rate (BuAc=1)	:	No information found.

SECTION 10 - STABILITY AND REACTIVITY

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products

Burning may produce carbon monoxide, carbon dioxide, nitrogen oxides.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Oxidizing agents, acids, acrylaldehyde, fluorine, chlorine, mercury, and maleic anhydride. It will attack some forms of plastics, rubber, and coating.

Conditions to Avoid:

Heat, flames, ignition sources and incompatibles.

SECTION 11 - TOXICOLOGICAL INFORMATION

Oral rat LD50: 698 mg/kg; inhalation rat LC50: 4540 ppm/6H; investigated as a mutagen.

NTP Carcinogen

Ingredient	:	Dimethylamine (124-40-3)
Known	:	No
Anticipated	:	No

IARC Category : None
Ingredient : Water (7732-18-5)
Known : No
Anticipated : No
IARC Category : None

SECTION 12 - ECOLOGICAL INFORMATION

Environmental Fate:

When released into the soil, this material is expected to quickly evaporate. When released into the soil, this material may leach into groundwater. When released into the soil, this material may biodegrade to a moderate extent. When released into water, this material is expected to readily biodegrade. When released into the water, this material is expected to have a half-life between 1 and 10 days. This material has an estimated bioconcentration factor (BCF) of less than 100. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material is expected to have a half-life of less than 1 day. When released into the air, this material is expected to be readily removed from the atmosphere by wet deposition.

Environmental Toxicity:

No information found.

SECTION 13 - DISPOSAL CONSIDERATIONS

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements

SECTION 14 - TRANSPORT INFORMATION

Domestic (Land, D.O.T.)

Proper Shipping Name : DIMETHYLAMINE SOLUTION
Hazard Class : 3, 8
UN/NA : UN1160
Packing Group : II
Information reported for product/size : 3KG

International (Water, I.M.O.)

Proper Shipping Name : DIMETHYLAMINE, AQUEOUS SOLUTION
Hazard Class : 3, 8
UN/NA : UN1160
Packing Group : II
Information reported for product/size : 3KG

SECTION 15 - REGULATORY INFORMATION

Chemical Inventory Status - Part 1

Ingredient : Dimethylamine (124-40-3)
TSCA : Yes
EC : Yes
Japan : Yes
Australia : Yes

Ingredient : Water (7732-18-5)
TSCA : Yes
EC : Yes
Japan : Yes
Australia : Yes

Chemical Inventory Status - Part 2

Ingredient : Dimethylamine (124-40-3)

Canada :
Korea : Yes
DSL : Yes
NDSL : No
Phil : Yes

Ingredient : Water (7732-18-5)

Canada :
Korea : Yes
DSL : Yes
NDSL : No
Phil : Yes

Federal, State & International Regulations - Part 1

Ingredient : Dimethylamine (124-40-3)

SARA 302
RQ : No
TPQ : No

SARA 313
List : Yes
Chemical Catg: No

Ingredient : Water (7732-18-5)

SARA 302
RQ : No
TPQ : No

SARA 313
List : No
Chemical Catg: No

Federal, State & International Regulations - Part 2

Ingredient : Dimethylamine (124-40-3)
CERCLA : 1000

RCRA
261.33 : U092

TSCA
8(d) : No

Ingredient : Water (7732-18-5)
CERCLA : No

RCRA
261.33 : No

TSCA
8(d) : No

Chemical Weapons Convention : Yes TSCA 12(b): No CDTA: No
SARA 311/312 : Acute: Yes Chronic: Yes Fire: Yes Pressure: No
Reactivity : No (Mixture / Liquid)

Australian Hazchem Code : 2PE
Poison Schedule : None allocated.

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

SECTION 16 - OTHER INFORMATION

NFPA Ratings: Health: 3 Flammability: 3 Reactivity: 0

Label Hazard Warning:

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. CAUSES BURNS TO ANY AREA OF CONTACT.

Label Precautions:

No SAF-T-DATA Ratings have been developed for this product. Read and follow all warnings, precautions, instructions and other safety and handling information on the label and MSDS

Do not breathe vapor.

Do not get in eyes, on skin, or on clothing.

Keep container closed.

Use only with adequate ventilation.

Wash thoroughly after handling.

Keep away from heat, sparks and flame.

Label First Aid:

In all cases call a physician immediately. If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse

Product Use:

Laboratory Reagent.

Revision Information:

MSDS Section(s) changed since last revision of document include: 8.

DISCLAIMER:

Mallinckrodt Baker, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT BAKER, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT BAKER, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

