

MATERIAL SAFETY DATA SHEET

CONTACT : **LEONID CHEMICALS**Leonid Chemicals Pvt Ltd
62/A-2 1st Stage, Yeshwanthpur Industrial Suburb
Ashokpuram School Road
Bangalore-560 022, Karnataka, INDIA
Ph: +91-80-2337 8354, Fax: +91-80-2357 4827

Produ	ct details:
Produ	ct name: <u>Trichlorophenylsilane</u>
Stock	number: 902
Manu	facturer/Supplier:
	D CHEMICALS
	2 2nd Stage, Industrial Suburb vanthpur, Bangalore -22, INDIA
	11-80-23378354.
- 2	Composition/Data on components:
•	Chemical characterization:
	Description: (CAS#)
	Trichlorophenylsilane (CAS# 98-13-5), 100%
•	Identification number(s):
•	EINECS Number: 202-640-8
	Hazards identification
	ndzards identification
•	Hazard description: C Corrosive
•	Information pertaining to particular dangers for man and environment
•	R 14 Reacts violently with water.
	R 20/21 Harmful by inhalation and in contact with skin.
	R 34 Causes burns.
•	Classification system
•	HMIS ratings (scale 0-4)
	(Hazardous Materials Identification System)
	Health (acute effects) = 3
	Flammability = 1
	Reactivity = 2



General information

Immediately remove any clothing soiled by the product.

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Seek immediate medical advice.

• After skin contact

Immediately wash with water and soap and rinse thoroughly. Seek immediate medical advice.

• After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing Seek immediate medical advice.

5 Fire fighting measures

Suitable extinguishing agents

CO2, sand, extinguishing powder. Do not use water.

- For safety reasons unsuitable extinguishing agents Water
- Special hazards caused by the material, its products of combustion or resulting gases:

Reacts violently with water

In case of fire, the following can be released:

Hydrogen chloride (HCl)

Carbon monoxide and carbon dioxide

Protective equipment:

Wear self-contained respirator.

Wear fully protective impervious suit.

6 Accidental release measures

Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Measures for environmental protection:

Do not allow material to be released to the environment without proper governmental permits.

Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Additional information:

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.



2

7 Handling and storage

• Handling

Information for safe handling:

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

• Information about protection against explosions and fires:

Keep ignition sources away.

Protect from heat.

Protect against electrostatic charges.

Protect from humidity and water.

Storage

• Requirements to be met by storerooms and receptacles:

No special requirements.

Information about storage in one common storage facility:

Store away from water/moisture.

Store away from oxidizing agents.

Do not store together with acids.

Do not store together with alkalies (caustic solutions).

Further information about storage conditions:

Protect from humidity and water.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

Store under lock and key and with access restricted to technical experts or their assistants only.

8 Exposure controls and personal protection

Additional information about design of technical systems:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Components with limit values that require monitoring at the workplace:

Not required.

- Additional information: No data
- Personal protective equipment

General protective and hygienic measures

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

Use suitable respirator when high concentrations are present.

- Protection of hands: Impervious gloves
- Eye protection:

Safety glasses



Tightly sealed goggles Full face protection

• Body protection: Protective work clothing.

9 Physical and chemical properties:

- General Information
- Form: LiquidColor: ColorlessOdor: Acidic
- <u>Value/Range Unit Method</u>
- Change in condition
- Melting point/Melting range: -127 ° C
 Boiling point/Boiling range: 201 ° C
 Sublimation temperature / start: Not determined
- Flash point: 91 ° C
- Ignition temperature: Not determined
- Decomposition temperature: Not determined
- Danger of explosion:

 Draduct does not present an explosion.
- Product does not present an explosion hazard.
- Explosion limits:
- Lower: Not determinedUpper: Not determined
- Vapor pressure: at 33 ° C
 1.33 hPa
- **Density:** at 20 ° C 1.324 g/cm³
- Solubility in / Miscibility with
- Water: Reacts violently Not miscible or difficult to mix

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided:
 - Decomposition will not occur if used and stored according to specifications.
- Materials to be avoided:

Water/moisture Oxidizing agents

Acids

Bases

• Dangerous reactions Reacts violently with water



• Dangerous products of decomposition:

Hydrogen chloride (HCl)
Carbon monoxide and carbon dioxide

11 Toxicological information

Acute toxicity:

LD/LC50 values that are relevant for classification:

Dermal: LD50: 890 µg/kg (rbt)

Inhalative: LC50/2H: 330 mg/m3/2H (mus) Irritation of skin: severe: 5 mg/24H (rbt)

- Primary irritant effect:
- on the skin:

Corrosive effect on skin and mucous membranes.

Irritant to skin and mucous membranes.

on the eye:

Strong corrosive effect.

Irritating effect.

- **Sensitization:** No sensitizing effects known.
- Subacute to chronic toxicity:

Organic silicon compounds are generally of low toxicity. Those exhibiting moisture sensitivity may be strongly irritating or corrosive on contact.

Subacute to chronic toxicity:

Corrosive materials are acutely destructive to the respiratory tract, eyes, skin and digestive tract. Eye contact may result in permanent damage and complete vision loss. Inhalation may result in respiratory effects such as inflammation, edema, and chemical pneumonitis. May cause coughing, wheezing, laryngitis, shortness of breath, headache, nausea and vomiting. Ingestion may cause damage to the mouth, throat and esophagus. May cause skin burns or irritation depending on the severity of the exposure.

Additional toxicological information:

Danger through skin absorption.

Swallowing will lead to a strong corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.

12 Ecological information:

• General notes:

Do not allow material to be released to the environment without proper governmental permits.

13 Disposal considerations

• Product:



5

• Recommendation

Consult state, local or national regulations to ensure proper disposal.

- Uncleaned packagings:
- Recommendation:

Disposal must be made according to official regulations.

□ 14 Transport information

- DOT regulations:
- Hazard class:
- Identification number: UN3094
- Packing group:
- Proper shipping name (technical name):

Corrosive liquid, water-reactive, n.o.s., trichlorophenylsilane

- Land transport ADR/RID (cross-border)
- ADR/RID class: 8 Corrosive substances
- Item: 72b
- Danger code (Kemler): 823
- UN-Number: 3094
- **Description of goods:** Corrosive liquid, water-reactive, n.o.s., trichlorophenylsilane
- Maritime transport IMDG:
- IMDG Class: 8
- UN Number: 3094
- Packaging group:
- **Proper shipping name:** Corrosive liquid, water-reactive, n.o.s., trichlorophenylsilane
- Air transport ICAO-TI and IATA-DGR:
- ICAO/IATA Class: 8
 UN/ID Number: 3094
 Packaging group: II
- Proper shipping name: Corrosive liquid, water-reactive, n.o.s., trichlorophenylsilane

15 Regulations

- Product related hazard informations:
- Hazard symbols: C Corrosive
- Risk phrases:
 - 14 Reacts violently with water.
 - 20/21 Harmful by inhalation and in contact with skin.
 - 34 Causes burns.



Safety phrases:

- 4 Keep away from living quarters.
- 8 Keep container dry.
- 9 Keep container in a well-ventilated place.
- When using do not eat or drink.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 30 Never add water to this product.
- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 45 In case of accident or if you feel unwell, seek medical advice immediately.
- This material and its container must be disposed of as hazardous waste.

• National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.

Information about limitation of use:

For use only by technically qualified individuals.

16 Other information:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

- Department issuing MSDS: Health, Safety and Environmental Department.
- Contact: Darrell R. Sanders

