

Quality Assurance Department

An ISO-9001:2008 Certified Company

(CODE) DOCUMENT: WI

(CODE) SECTION : WI/SM

(DATE): 01.04.2011



Issue : 02 Rev.: 00

1 | Pageof1

Product name:

1-Butanol

Cat No: B026

Synonyms:

Butyl alcohol, n-Butanol

Title: MATERIAL SAFETY DATA SHEET (MSDS): 1-BUTANOL

CAS-No.: 71-36-3

Company Information:

LEONID CHEMICALS Pvt Ltd,

62/A2,1st Stage,

Yeshvanthpur Industrial Suburb,

Asoka puram School Road,

Bangalore -22, Karnataka, INDIA

Ph- +91-80-23378354

Fax: +918023378354/23377126

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [EU-GHS/CLP]

Flammable liquids (Category 3)

Acute toxicity, Oral (Category 4)

Specific target organ toxicity - single exposure (Category 3)

Skin irritation (Category 2)

Serious eve damage (Category 1)

Specific target organ toxicity - single exposure (Category 3)

Classification according to EU Directives 67/548/EEC or 1999/45/EC

Flammable. Harmful if swallowed. Irritating to respiratory system and skin. Risk of serious damage to eyes.

Vapours may cause drowsiness and dizziness.

Label elements

Labelling according Regulation (EC) No 1272/2008 [CLP]

Pictogram



Quality Assurance Department

An ISO-9001:2008 Certified Company

(CODE) DOCUMENT: WI

(CODE) SECTION: WI/SM
(DATE): 01.04.2011



Issue : 02

Rev.: 00

2 | Pageof1

Signal word Danger

Hazard statement(s)

H226 Flammable liquid and vapour.

Title: MATERIAL SAFETY DATA SHEET (MSDS): 1-BUTANOL

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/ eye protection/ face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Supplemental Hazard

Statements

none

According to European Directive 67/548/EEC as amended.

Hazard symbol(s)

R-phrase(s)

R10 Flammable.

R22 Harmful if swallowed.

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

R67 Vapours may cause drowsiness and dizziness.

S-phrase(s)

\$ 7/9 Keep container tightly closed and in a well-ventilated place.

\$13 Keep away from food, drink and animal feeding stuffs.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

\$37/39 Wear suitable gloves and eye/face protection.

S46 If swallowed, seek medical advice immediately and show this container or label.

Other hazards - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula: C₄H₁₀O

Molecular Weight: 74.12 g/mol

CAS-No.: 71-36-3

4. FIRST AID MEASURES

Description of first aid measures



Quality Assurance Department

An ISO-9001:2008 Certified Company

(CODE) DOCUMENT: WI

(CODE) SECTION : WI/SM

(DATE): 01.04.2011



Issue : 02

Rev.: 00

3 | Pageof1

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Title: MATERIAL SAFETY DATA SHEET (MSDS): 1-BUTANOL

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Most important symptoms and effects, both acute and delayed drying, cracking of the skin, Skin irritation

Indication of any immediate medical attention and special treatment needed no data available

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special hazards arising from the substance or mixture

Carbon oxides

Advice for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Further information

In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Reference to other sections



An ISO-9001:2008 Certified Company

(CODE) DOCUMENT: WI

(CODE) SECTION : WI/SM (DATE) : 01.04.2011



Issue : 02

Rev.: 00

4 | Pageof1

Quality Assurance Department

Title: MATERIAL SAFETY DATA SHEET (MSDS): 1-BUTANOL

For disposal see section 13.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Handle and store under inert gas. hygroscopic

Specific end uses

no data available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Components with workplace control parameters

Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique

(without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.

Wash and dry hands.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection



An ISO-9001:2008 Certified Company

(CODE) DOCUMENT: WI

(CODE) SECTION: WI/SM

(DATE): 01.04.2011

MOODY INTERNATIONAL

Issue : 02

Rev.: 00

5|Pageof1

Quality Assurance Department

Title: MATERIAL SAFETY DATA SHEET (MSDS): 1-BUTANOL

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

a) Appearance Form: liquid, clear

Colour: colourless

b) Odour no data available

c) Odour Threshold: no data available

d) pH: no data available

e) Melting point/freezing point Melting point/range: -90 °C

f) Initial boiling point and boiling range: 116 - 118 °C

g) Flash point: 35 °C - closed cup

h) Evaporation rate: no data available

i) Flammability (solid, gas): no data available

i) Upper/lower flammability or explosive limits

Upper explosion limit: 11.2 %(V) Lower explosion limit: 1.4 %(V)

k) Vapour pressure: 5 hPa at 20 °C

I) Vapour density 2.56 - (Air = 1.0)

m) Relative density: 0.81 g/mL at 25 °C

n) Water solubility: soluble

o) Partition coefficient: noctanol/water: no data available

p) Autoignition temperature: no data available

g) Decomposition temperature: no data available

r) Viscosity: no data available

s) Explosive properties: no data available

t) Oxidizing properties: no data available

Other safety information

no data available

10. STABILITY AND REACTIVITY

Reactivity
no data available
Chemical stability
no data available
Possibility of hazardous reactions



An ISO-9001:2008 Certified Company

(CODE) DOCUMENT: WI

(CODE) SECTION: WI/SM

(DATE): 01.04.2011

Issue: 02

Rev.: 00

6 | Pageof1

Quality Assurance Department

Title: MATERIAL SAFETY DATA SHEET (MSDS): 1-BUTANOL

no data available

Conditions to avoid

Exposure to moisture.

Heat, flames and sparks.

Incompatible materials

Oxidizing agents, Alkali metals, Bases, Strong acids, Halogens

Hazardous decomposition products

Other decomposition products - no data available

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity

LD50 Oral - rat - 790 mg/kg

Remarks: Liver: Fatty liver degeneration. Kidney, Ureter, Bladder: Other changes. Blood:

Other changes.

LC50 Inhalation - rat - 4 h - 8000 ppm LD50 Dermal - rabbit - 3.400 mg/kg

Skin corrosion/irritation

Skin - rabbit - Skin irritation - 24 h Serious eye damage/eye irritation

Eyes - rabbit - Eye irritation

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

no data available

Specific target organ toxicity - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

no data available

Aspiration hazard

no data available

Potential health effects

Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause drowsiness and dizziness.

Ingestion Harmful if swallowed.



An ISO-9001:2008 Certified Company

(CODE) DOCUMENT: WI

(CODE) SECTION : WI/SM
(DATE) : 01.04.2011



Issue : 02

Rev.: 00

7 | Pageof1

Quality Assurance Department

Title: MATERIAL SAFETY DATA SHEET (MSDS): 1-BUTANOL

Skin May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes serious eye irritation.
Signs and Symptoms of Exposure drying, cracking of the skin, Skin irritation
Additional Information
RTECS: E01400000

12. ECOLOGICAL INFORMATION

Toxicity

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 1.840 mg/l - 96 h Toxicity to daphnia and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 1.983 mg/l - 48 h

Persistence and degradability

Bioaccumulative potential

Bioaccumulation Oncorhynchus mykiss (rainbow trout) - 24 h -921 mg/l

Bioconcentration factor (BCF): 0,38

Mobility in soil

no data available

Results of PBT and vPvB assessment

no data available

Other adverse effects

no data available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

UN number

ADR/RID: 1120 IMDG: 1120 IATA: 1120

UN proper shipping name

ADR/RID: BUTANOLS IMDG: BUTANOLS IATA: Butanols



Quality Assurance Department

An ISO-9001:2008 Certified Company

(CODE) DOCUMENT: WI

(CODE) SECTION : WI/SM

(DATE): 01.04.2011



Issue : 02

Rev.: 00

8 Pageof1

Transport hazard class(es)
ADR/RID: 3 IMDG: 3 IATA: 3

Title: MATERIAL SAFETY DATA SHEET (MSDS): 1-BUTANOL

Packaging group

ADR/RID: III IMDG: III IATA: III Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

Special precautions for user

no data available

15. REGULATORY INFORMATION

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Safety, health and environmental regulations/legislation specific for the substance or mixture no data available

Chemical Safety Assessment no data available

16. OTHER INFORMATION

Further information

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Leonid Chemicals Pvt. Ltd. be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Leonid Chemicals Pvt. Ltd. has been advised of the possibility of such damages.

